


CAT 6 600MHz UTP PLENUM (CMP) 23/4 UNSHIELDED FT6 Cable

Cable Detail



Applicable Standards

- C(ETL) listed FT6 CMP
- C(ETL)US Verified to TIA-568-C.2
- RoHS Compliant



Physical Characteristics

Conductor Material	Solid Bare Copper
Number of Conductors	4
AWG	23 AWG
Stranding	Solid
Insulation Material	FEP
Overall Diameter	0.038 in. $\pm$ 0.0002 in
Average Thickness	0.0078 in
Jacket Material	Flame Retardant PVC
Average Wall Thickness	0.020 in.
Nominal Outer Diameter	0.236 in. $\pm$ 0.008 in.
Nominal Weight	31 lbs.
Shielding (Y/N)	No
Ripcord (Y/N)	Yes
Separator (Y/N)	Yes

Mechanical Characteristics

Temperature Range	Installation	0°C to + 75°C
	Operating	-20°C to + 75°C
Tensile Strength	Before	$\geq$ 13.8 Mpa
Elongation	Aging	$\geq$ 100%
Aging Condition		100°C x 168 hours
	After	$\geq$ 85% of unaged
	Aging	$\geq$ 50% of unaged

Insulation Colors

Pair 1	White / Blue	Blue
Pair 2	White / Orange	Orange
Pair 3	White / Green	Green
Pair 4	White / Brown	Brown

Part Numbers

Jacket Color

Package

6E04UPXX3N

Blue, Grey, Red, Purple,
White

1000FT / RIB

6E04UPXX4N

Black, Blue, Green, Grey, Red,
Orange, Purple, White, Yellow

1000FT / Reelex II

Electrical Characteristics

DC Resistance	9.38 Ω / 100m Max. @ 20°C
Resistance Unbalanced	5% Max. @ 20°C
Capacitance Unbalance	330 pF / 100m Max. @ 20°C
Mutual Capacitance	5.6 nF / 100m Max. @ 20°C
Delay Skew	45 nS / 100m Max. @ 20°C
Nominal Velocity of Propagation (NVP)	70%

Electrical Performance

Frequency (MHz)	Attenuation (dB/100m) Max.	Return loss (dB) Min.	NEXT (dB) Min.	PS-NEXT (dB) Min.
1	2.0	20.0	77.3	75.3
4	3.8	23.6	68.3	66.3
8	5.3	25.4	63.8	61.8
10	5.9	26.0	62.3	30.3
16	7.4	26.0	59.3	57.3
20	8.3	26.0	57.8	55.8
25	9.3	25.5	56.3	54.3
31.25	10.4	25.0	54.9	52.9
62.5	14.9	23.5	50.4	48.4
100	19.0	22.5	47.3	45.3
155	23.9	21.6	45.8	43.5
200	27.4	21.0	42.8	40.8
250	30.8	20.5	41.3	39.3
300	34.0	20.1	40.2	38.2
350	37.0	19.8	39.2	37.2
400	39.7	19.5	38.3	36.3
450	42.1	19.2	37.5	35.5
500	44.9	19.0	36.8	34.8
550	47.3	18.8	36.2	34.2
600				
Frequency (MHz)	ELFEXT (dB/100m) Min.	PS-ELFEXT (dB) Min.	ACR (dB) Min.	PS-ACR (dB) Min.
1	70.8	67.8	75.0	73.0
4	58.7	55.7	64.0	62.0
8	52.7	49.7	57.7	55.7
10	50.8	47.8	55.6	53.6
16	46.7	43.7	50.7	48.7
20	44.7	41.7	48.2	16.2
25	42.8	39.8	45.6	13.6
31.25	40.9	37.9	42.8	40.8
62.5	34.8	31.8	32.9	30.9
100	30.8	27.8	24.9	22.9
155	27.0	23.6	21.0	21.5
200	24.7	21.7	18.4	16.4
250	22.8	19.8	13.5	11.5
300	21.2	18.2	9.6	5.0
350	19.9	16.9	5.2	3.2
400	18.7	15.7	1.5	-
450	17.7	14.7	-	-
500	16.8	13.8	-	-
550	15.9	12.9	-	-
600				

* Values above 250MHz are information only.

Cable Marking

XXXXXX CATEGORY 6 600MHZ 23AWG 4PR UTP CMP 75C FT6 C(ETL)US
VERIFIED (ETL) ANSI/TIA-568-C.2 *****FT

