


CAT 6 600MHz FTP RISER (CMR) 23/4 SHIELDED FT4 CABLE

Cable Detail



Applicable Standards

- C(ETL) listed FT4 CMR
- C(ETL)US Verified to TIA-568-C.2
- RoHS Compliant



Physical Characteristics

Conductor Material	Solid Bare Copper
Number of Conductors	4
AWG	23 AWG
Stranding	Solid
Insulation Material	HDPE
Overall Diameter	0.045 in. $\pm$ 0.0002 in
Average Thickness	0.0106 in
Jacket Material	Flame Retardant PVC
Average Wall Thickness	0.0236 in.
Nominal Outer Diameter	0.2992 in. $\pm$ 0.008 in.
Nominal Weight	37 lbs.
Shielding (Y/N)	Yes (AL-Foil)
Ripcord (Y/N)	Yes
Separator (Y/N)	Yes

Mechanical Characteristics

Temperature Range	Installation	0°C to + 75°C
	Operating	-20°C to + 75°C
Tensile Strength	Before	$\geq$ 13.8 Mpa
Elongation	Aging	$\geq$ 100%
Aging Condition		100°C x 168 hours
	After	$\geq$ 85% of unaged
	Aging	$\geq$ 50% of unaged

Insulation Colors

Pair 1	White / Blue	Blue
Pair 2	White / Orange	Orange
Pair 3	White / Green	Green
Pair 4	White / Brown	Brown

Part Numbers	Jacket Color	Package
6E04SRXX2N	Black, Blue, Green, Grey, Red, White, Yellow, Purple	1000FT / Reel

Electrical Characteristics

DC Resistance	9.38 Ω / 100m Max. @ 20°C
Resistance Unbalanced	5% Max. @ 20°C
Capacitance Unbalance	330 pF / 100m Max. @ 20°C
Mutual Capacitance	5.6 nF / 100m Max. @ 20°C
Delay Skew	45 nS / 100m Max. @ 20°C
Nominal of Propagation	69%

Electrical Performance

Frequency (MHz)	Attenuation (dB/100m) Max.	Return loss (dB) Min.	NEXT (dB) Min.	PS-NEXT (dB) Min.
1	2.03	20.0	74.3	72.3
4	3.87	23.0	65.3	63.3
10	5.95	25.0	59.3	57.3
16	7.55	25.0	56.2	54.2
20	8.47	25.0	54.8	52.8
25	9.51	24.3	53.3	51.3
31.25	10.67	23.6	51.9	49.9
62.5	15.38	21.5	50.4	45.4
100	19.80	20.1	47.4	51.3
200	28.98	18.0	44.3	37.8
250	32.85	17.3	39.8	36.3
300	34.00	20.1	38.3	38.2
350	37.00	19.8	40.2	37.2
400	39.70	19.5	38.3	36.3
450	42.10	19.2	37.5	35.5
500	44.90	19.0	36.8	34.8
550	47.30	18.8	36.2	34.2
600	50.7	15.7	44.2	42.2
Frequency (MHz)	ELFEXT (dB/100m) Min.	PS-ELFEXT (dB) Min.	Delay (ns/100m) Max.	ACR (dB)
1	67.80	64.80	570.00	72.70
4	55.76	52.76	552.00	61.40
10	47.80	44.80	545.38	53.35
16	43.72	40.72	543.00	48.69
20	41.78	38.78	542.05	46.31
25	39.84	36.84	541.20	43.82
31.25	37.90	34.90	540.44	41.21
62.5	31.88	28.88	538.55	31.98
100	27.80	24.80	537.60	24.50
200	21.78	18.78	536.55	10.80
250	19.84	16.84	536.28	5.40
300	21.20	18.20	-	-
350	19.90	16.90	-	-
400	18.70	15.70	-	-
450	17.70	14.70	-	-
500	16.80	13.80	-	-
550	15.90	12.90	-	-
600	N/A	N/A	N/A	N/A

* Values above 250MHz are information only.

Cable Marking

XXXXXX CATEGORY 6 600MHz 23AWG 4PR FTP CMR 75C FT4 C(ETL)US
VERIFIED (ETL) ANSI/TIA-568-C.2 ****FT

