

# 14AWG/4C Stranded Riser (CMR) Audio Cable

## Cable Detail



## Approval



## Description

- 14/4 Stranded CMR/CL3R Sound Audio Cable

## Applicable Standards

- For Communication and Signal Control Systems
- 4 Oxygen Free Bare Copper Conductors in an Overall Jacket

## Physical Characteristics

| Conductor            | Oxygen Free B.C. |
|----------------------|------------------|
| Number of Conductor  | 4                |
| AWG                  | 14               |
| Stranding            | 105              |
| Diameter             | 0.0063 (inches)  |
| Insulation Material  | PVC              |
| Diameter             | 0.1023 (inches)  |
| Average Thickness    | 0.014 (inches)   |
| Min. Point Thickness | 0.013 (inches)   |
| Assembly Diameter    | 0.248 (inches)   |
| Jacket Material      | PVC              |
| Outer Diameter       | 0.3149 (inches)  |
| Average Thickness    | 0.0315 (inches)  |
| Min. Point Thickness | 0.0283 (inches)  |
| Rip Cord             | Nylon            |
| Conductor Resistance | 9.2 (ohms)       |
| Nominal Weight       | 42 (pounds)      |

## Colors

- Insulation Color  
Black / Red / White / Green
- Jacket Color  
Black, White

## Part Number

AC1404RBK3-500  
AC1404RWH3-500

## Package

500FT / REELEX II

## Cable Marking

AUDIO CABLE 4 COND 14AWG HI-STRAND OFC  
CMR/CL3R FT4 75C EXXXXXX C(ETL)US \*\*\*FT