

# 22AWG/6C Stranded Shielded Riser (CMR) Security Cable

## Cable Detail



## Approval



## Description

- 22/6 Shielded Stranded Bare Copper CMR Security Cable

## Applicable Standards

- Class 2 Power Limited Circuit Cable and Communications
- Cable for General Purpose Application

## Physical Characteristics

Conductor	Stranded Bare Copper
Number of Strands	7
Number of Conductor	6
AWG	22
Insulation Material	Polyvinyl Chloride (PVC)
Insulation Diameter	0.007" (mm)
Colors	Green / Red / Black / White / Brown / Blue
Shield	Low Smoke Aluminum Mylar
Drain Wire	24 AWG Tinned Copper
PE Tape	Yes
AL Foil Shield	Yes
Jacket Material	FR-(PVC)
Thickness	0.015" (0.38mm)
Nominal Outer Diameter	0.163" (4.14mm)
Rip Cord	Yes

Electrical Performance	
Rated Temperature	-20C to 75C
Voltage Rating	300V RMS
Nominal Weight	28 (pounds)

## Colors

- Insulation Color  
Green / Red / Black / White / Brown / Blue
- Jacket Color  
White

## Part Number

SC2206SRWH1-S

## Package

1000FT / REELEX II

## Cable Marking

22AWG 6 COND STRANDED SHIELDED XXXXXXXX CMR FT4  
C(ETL)US \*\*\*\*FT