

14AWG/2C Stranded UV Rated Direct Burial Audio Cable

Cable Detail



Approval



Description

- 14/2 Stranded CMR/CL3R Direct Burial Sound Audio Cable

Applicable Standards

- For Communication and Signal Control Systems
- 2 Oxygen Free Bare Copper Conductors in an Overall Jacket

Physical Characteristics

Conductor	Oxygen Free B.C.
Number of Conductor	2
AWG	14
Stranding	105
Diameter	0.0063 (inches)
Insulation Material	PVC
Diameter	0.1023 (inches)
Nominal Wall	0.0102 (inches)
Jacket Material	FR-PVC
Overall Diameter	0.2559 (inches)
Nominal Thickness	0.0196 (inches)
Paper Tape	YES
Rip Cord	YES
Conductor Resistance	10 (ohms/1000m)
Voltage	300 (volts)
Nominal Weight	27 (pounds)

Colors

- Insulation Color
Black / Red
- Jacket Color
Black

Part Number

AC1402OSPBK4-500

Package

500FT / REELEX II

Cable Marking

AUDIO CABLE 2 COND 14 AWG HI-STRAND OXYGEN FREE COPPER CMR/CL3R DIRECT BURIAL AUDIO CABLE SUN RES EXXXXXX C(ETL)US ***FT