


CAT 6 600MHz UTP CABLE

DIRECT BURIAL OUTDOOR (WATERBLOCK PE)

Cable Detail



Applicable Standards

- UL444 (Mechanical Properties only)
- TIA-568-C.2
- RoHS Compliant



Physical Characteristics

Conductor Material	Solid Bare Copper
Number of Conductors	4
AWG	23 AWG
Stranding	Solid
Fill Type	WaterBlock
Insulation Material	HDPE
Overall Diameter	0.040 in. $\pm$ 0.0002 in
Average Thickness	0.0088 in
Jacket Material	LLDPE, Sunlight Resistant
Average Wall Thickness	0.031 in.
Nominal Outer Diameter	0.318 in. $\pm$ 0.008 in.
Nominal Weight	32 lbs.
Shielding (Y/N)	No
Ripcord (Y/N)	Yes
Separator (Y/N)	Yes

Mechanical Characteristics

Temperature Range	Installation	0°C to + 75°C
	Operating	-20°C to + 75°C
Tensile Strength	Before	$\geq$ 19 Mpa
Elongation	Aging	$\geq$ 300%
Aging Condition		100°C x 96 hours
	After	$\geq$ 85% of unaged
	Aging	$\geq$ 50% of unaged

Insulation Colors

Pair 1	White / Blue	Blue
Pair 2	White / Orange	Orange
Pair 3	White / Green	Green
Pair 4	White / Brown	Brown

Part Numbers

Jacket Color

Package

6EOSPBK2N

Black

1000FT / Reel

Electrical Characteristics

DC Resistance	9.38 Ω / 100m Max. @ 20°C
Resistance Unbalanced	5% Max. @ 20°C
Capacitance Unbalance	330 pF / 100m Max. @ 20°C
Mutual Capacitance	5.6 nF / 100m Max. @ 20°C
Delay Skew	45 nS / 100m Max. @ 20°C
Nominal Velocity of Propagation (NVP)	69%

Electrical Performance

Frequency (MHz)	Attenuation (dB/100m) Max.	Return loss (dB) Min.	NEXT (dB) Min.	PS-NEXT (dB) Min.
1	2.03	20.00	74.30	72.30
4	3.78	23.01	65.27	63.27
10	5.95	25.00	59.30	57.30
16	7.55	25.00	56.24	54.24
20	8.47	25.00	54.78	52.78
25	9.51	24.32	53.33	51.33
31.25	10.67	23.64	51.88	49.88
62.5	15.38	21.54	47.36	45.36
100	19.80	20.11	44.30	51.30
200	28.98	18.00	39.78	37.78
250	32.85	17.32	38.33	36.33
350	39.79	16.30	36.14	34.14
550	51.76	14.92	36.20	31.19
600	54.50	18.80	37.60	35.60
Frequency (MHz)	ELFEXT (dB/100m) Min.	PS-ELFEXT (dB) Min.	Delay (ns/100m) Max.	ACR (dB)
1	67.80	64.80	570.00	72.70
4	55.76	52.76	552.00	61.40
10	47.80	44.80	545.38	53.35
16	43.72	40.72	543.00	48.69
20	41.78	38.78	542.05	46.31
25	39.84	36.84	541.20	43.82
31.25	37.90	34.90	540.44	41.21
62.5	31.88	28.88	538.55	31.98
100	27.80	24.80	537.60	24.50
200	21.78	18.78	536.55	10.80
250	19.84	16.84	536.28	5.40
350	16.92	13.92	535.92	-3.65
550	12.99	9.99	535.54	-18.57
600	15.90	12.90	17.20	14.20

* Values above 250MHz are information only.

Cable Marking

 CATEGORY 6 600MHZ 23AWG 4PR UTP DIRECT BURIAL OUTDOOR
 WATERBLOCK TIA-568-C.2 ****FT
