


# 22AWG/4C Solid Unshielded Riser (CMR) Security Cable

## Cable Detail



## Approval



## Description

- 22/4 Solid Bare Copper CMR Security Cable

## Applicable Standards

- Class 2 Power Limited Circuit Cable and Communications
- Cable for General Purpose Application

## Physical Characteristics

| Conductor                        | Bare Copper              |
|----------------------------------|--------------------------|
| Number of Conductor              | 4                        |
| AWG                              | 22                       |
| Diameter                         | 0.61 (mm)                |
| Insulation Material              | Polyvinyl Chloride (PVC) |
| Insulation Diameter              | 0.96 (mm)                |
| Colors                           | Red, Black, White, Green |
| Jacket Material                  | Polyvinyl Chloride (PVC) |
| Thickness                        | 0.45 (mm)                |
| Overall Diameter                 | 3.20 (mm)                |
| Rip Cord                         | Yes                      |
| Electrical & Physical Properties |                          |
| Voltage                          | 300V RMS                 |
| Temperature Rating               | 75C                      |

## Colors

- Insulation Color  
Green / White / Black / Red
- Jacket Color  
Grey, White

## Part Number

SC2204RGY1  
SC2204RGY-500  
SC2204RWH1  
SC2204RWH-500

## Package

500FT / COIL PACK  
1000FT / REELEX II

## Cable Marking

22AWG 4 COND SOLID XXXXXXXX CMR FT4 C(ETL)US  
\*\*\*FT