

16AWG/2C OFC Stranded Riser (CMR) Audio Cable

Cable Detail



Approval



Description

- 16/2 Stranded CMR/CL3R Sound Audio Cable

Applicable Standards

- For Communication and Signal Control Systems
- 2 Oxygen Free Bare Copper Conductors in an Overall Jacket

Physical Characteristics

| Conductor | Oxygen Free B.C. |
|----------------------|------------------|
| Number of Conductor | 2 |
| AWG | 16 |
| Stranding | 65 |
| Diameter | 0.0063 (inches) |
| Insulation Material | PVC |
| Diameter | 0.0827 (inches) |
| Average Thickness | 0.0122 (inches) |
| Min. Point Thickness | 0.0106 (inches) |
| Assembly Diameter | 0.1614 (inches) |
| Jacket Material | PVC |
| Outer Diameter | 0.2008 (inches) |
| Average Thickness | 0.0197 (inches) |
| Min. Point Thickness | 0.0177 (inches) |
| Rip Cord | Nylon |
| Conductor Resistance | 15.5 (ohms) |
| Nominal Weight | 15 (pounds) |
| Voltage Rating | 300V (volts) |

Colors

- Insulation Color
Black / Red
- Jacket Color
Black, White

Part Number

AC1602RBK4-500
AC1602RWH4-500

Package

500FT / REELEX II

Cable Marking

AUDIO CABLE 2 COND 16AWG HI-STRAND OFC
CMR/CL3R FT4 75C EXXXXXX C(ETL)US ***FT